



Step 1

With your printer switched on hold down both the 'up' arrow and the 'down' arrow simultaneously for 10 seconds. (See Fig 1)

Release both buttons then quickly press the '#' button to access the service menu. (see Fig 2)

Fig. 3



Fig. 4



Step 3

The printer will then request an 'SP Number'.

Enter the Number 3008002 (Fig 5)

Use the 'up' arrow and 'down' arrow to select the number and the '#' button to move to the next digit.

The screen will then show RST:INIT CNT:A (Fig 6). Press the '#' button to progress to the next screen.

The printer will then ask you if you wish to execute this program (Fig 7). Use the '#, button to confirm. The screen will then ask you to confirm your choice; (Fig 8) press the '#' button again to confirm.

Once this has been completed press the 'left' arrow button to return to the service menu. Then use the 'down arrow' to select end.

Turn off the printer,

Ensure the sublisplash ink is installed in the ink bay

and turn the printer back on the printer will then say ink loading this will take about 6 mins to complete

Fig. 1



Fig. 2



Step 2

The screen on your printer will now display the message 'SYSTEMver Service Menu' (Fig 3).

Press the down arrow until you see 'Engine Maintenance' (fig 4).

Then press the '#' button.

Fig. 5



Fig. 6



Fig. 7



Fig. 8

